

## DIETER



DATE	
ITEM #	MT-DIETER
PROJECT	
COMMENTS	
PREPARED BY	

## DESCRIPTION

Round Tapered Pendant Light

## SPECIFICATION FEATURES

### MATERIAL / MOUNTING

Cold-rolled steel frame wire body.  
Matte white acrylic bottom diffuser (Optional).

### SHADES

Solid cold-rolled steel construction.  
Material on heavy translucent white styrene with your choice of the coverings opacity.

### FINISH

Standard: White (WHI)  
Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed Bronze (ORB)

### ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available, but may impact extended lead time and standard price.

### LIGHTING

3-way, standard socket cluster. Works with incandescent or LED bulbs.

### INSTALLATION

Easy-to-install. Attaches to standard 4" junction box. 120V power.  
Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

### OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

### USAGE

Approved for interior locations only.

### MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

# ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.  
Pre-selected values may also be modified, if required.

## DIETER

### SERIES

DIETER: Round Tapered  
Pendant Light

18

30

FC

#### SHADE TOP DIAMETER

IN INCHES

6, 8, 10, 12, 14, 16,  
18, 20, 22, 24, 26

30

#### SHADE BOTTOM DIAMETER

IN INCHES

6, 8, 10, 12, 14, 16,  
18, 20, 22, 24, 26

#### SHADE SLANT HEIGHT

IN INCHES

6, 8, 10, 12, 14, 16,  
18, 20, 22, 24, 26,  
28, 30, 32, 34, 36,  
38, 40, 42, 44, 46,  
48, 50, 52, 54, 56,  
58, 60

#### SUSPENSION STYLE

SRS: Swivel Rigid Stem

FS: Fixed Stem

FC: Flex Cord

AC: Aircraft Cable with  
Flex Cord

#### CANOPY COLOR

STANDARD

WHI: White

PREMIUM

NIC: Nickel

BRA: Brass

BLA: Black

IVO: Ivory

ORB: Oil-Rubbed Bronze

#### CORD COLOR

STANDARD

C-BLA: Black

C-WHI: White

#### CORD LENGTH

4FT: 4 Feet 12FT: 12 Feet

8FT: 8 Feet 16FT: 16 Feet

A

3

#### LAMP SHADE OPACITY

OPAQUE:

Features an interior  
light-blocking layer to  
make shade opaque. (No  
light passes through the  
sides of the shade)

TRANSLUCENT:

Shade covering allows  
some light to shine  
through.

VERTICAL TRIM:

1/2" trim applied to  
shade exterior over  
vertical support bars to  
hide shadows.

#### LAMP SHADE COVERING

STANDARD

(Some Examples)

L-CRE: Linen Cream

L-WHI: Linen White

PREMIUM

(Some Examples)

DL-OFF: Designer Linen

Off-White

VC-WHI: Vinyl Coated

White

#### ACRYLIC DIFFUSER

A: With Acrylic  
Diffuser

FBD: With Fabric  
Diffuser

NA: Without  
Acrylic Diffuser

#### LAMPING

Specify Number of  
Light Sockets

1, 2, 3, 5

#### BULBS

Number of Bulbs  
Depends on Socket

9W2700:

800 Lumens 2,700K

15W2700:

1,600 Lumens 2,700K

NA: No Bulbs