



## HENRY

DATE	
ITEM #	MT-HENRY
PROJECT	
COMMENTS	
PREPARED BY	

## DESCRIPTION

Round Drum Pendant Light

## SPECIFICATION FEATURES

### MATERIAL / MOUNTING

Cold-rolled steel frame wire body.  
Matte white acrylic bottom diffuser (Optional).

### SHADES

Solid cold-rolled steel construction.  
Material on heavy translucent white styrene with your choice of the coverings opacity.

### FINISH

Standard: White (WHI)  
Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed Bronze (ORB)

### ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available, but may impact extended lead time and standard price.

### LIGHTING

5-way, standard socket cluster. Works with incandescent or LED bulbs.

### INSTALLATION

Easy-to-install. Attaches to standard 4" junction box. 120V power.  
Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

### OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

### USAGE

Approved for interior locations only.

### MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

# ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.  
Pre-selected values may also be modified, if required.

## HENRY

### SERIES

HENRY: Round Drum  
Pendant Light

30

8

FC

<u>SHADE DIAMETER</u>	<u>SHADE HEIGHT</u>	<u>SUSPENSION STYLE</u>	<u>CANOPY COLOR</u>	<u>CORD COLOR</u>
IN INCHES 6, 8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36	IN INCHES 6, 8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, 50, 52, 54, 56, 58, 60	SRS: Swivel Rigid Stem FS: Fixed Stem FC: Flex Cord AC: Aircraft Cable with Flex Cord	STANDARD WHI: White PREMIUM NIC: Nickel BRA: Brass BLA: Black IVO: Ivory ORB: Oil-Rubbed Bronze	STANDARD C-BLA: Black C-WHI: White
				<u>CORD LENGTH</u>
				4FT: 4 Feet 12FT: 12 Feet 8FT: 8 Feet 16FT: 16 Feet

A

1

<u>LAMP SHADE OPACITY</u>	<u>LAMP SHADE COVERING</u>	<u>ACRYLIC DIFFUSER</u>	<u>LAMPING</u>	<u>BULBS</u>
OPAQUE: Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade)	STANDARD (Some Examples) L-CRE: Linen Cream L-WHI: Linen White	A: With Acrylic Diffuser FBD: With Fabric Diffuser	Specify Number of Light Sockets 1, 2, 3, 5	Number of Bulbs Depends on Socket 9W2700: 800 Lumens 2,700K 15W2700: 1,600 Lumens 2,700K NA: No Bulbs
TRANSLUCENT: Shade covering allows some light to shine through. Vertical bars are exposed.	PREMIUM (Some Examples) DL-OFF: Designer Linen Off-White VC-WHI: Vinyl Coated White	NA: Without Acrylic Diffuser		
VERTICAL TRIM: 1/2" trim applied to shade exterior over vertical support bars to hide shadows.				